

UNITED STATES PATENT APPLICATION

of

Steven M. Horowitz

Geoffrey R. Smith

and

Peter J. Potrebic

for

BACKGROUND ENABLED RECORDING IN A SET TOP BOX

WORKMAN, NYDEGGER & SEELEY

A PROFESSIONAL CORPORATION

ATTORNEYS AT LAW

1000 EAGLE GATE TOWER

60 EAST SOUTH TEMPLE

SALT LAKE CITY, UTAH 84111

FILED " 69352260

BACKGROUND OF THE INVENTION

1. The Field of the Invention

The present invention relates to systems and methods for recording digital programming content included in a video stream or channel. More specifically, the present invention relates to systems and methods for recording a video stream or channel without degrading the quality of the video stream or channel at a set top box having at least one tuner.

2. The Prior State of the Art

Set top boxes, such as cable boxes and satellite receivers, are becoming increasingly prevalent in consumer's homes because they often provide a consumer with the ability to choose from a growing number of channels. Because the consumer has a great number of channels from which to choose, the consumer often has a desire to record a program on one of the channels for later viewing. As a result, many set top boxes have begun to resemble computers by providing a storage medium to the consumer such that the consumer may select and record programs that are received through set top boxes.

Recording a program usually results in a recording that is of lesser quality than the original program because the original program received by the set top box is decoded and re-encoded before it is actually recorded. This is because the digital transmission received by the set top box must be processed before a particular program or channel can be viewed or recorded. When the digital transmission is first received at the set top box, it must first be tuned to a particular transport stream. The transport stream contains multiple video streams, each of which corresponds to a particular channel. Thus, the transport stream is

1 demultiplexed to isolate or identify a single video stream. The demultiplexed video stream
2 contains related audio, video and data packets, which may be encrypted.

3
4 After the relevant video, audio and data packets for a particular channel have been
5 separated from the transport stream, a conditional access system determines whether or not
6 a consumer is authorized to access or display the demultiplexed channel. If the consumer
7 has authorized access to the channel, the affected packets are decrypted. Next, the
8 decrypted audio and video packets are decoded to produce video and audio outputs that
9 may be interpreted by a user device such as a television. Obviously, the conditional access
10 system does not operate when the demultiplexed channel or video stream is not encrypted.

11 In either case, the audio and video outputs of the satellite receiver provide the
12 consumer with access to the program that is to be recorded. Unfortunately, the audio and
13 video outputs of the satellite receiver are usually of an analog nature and cannot be
14 recorded digitally. To record a particular video stream or channel, a digital video recorder
15 or other recording device is often used in conjunction with a satellite receiver. The analog
16 inputs to the digital video recorder can be provided from a number of different sources
17 including satellite receivers and cable boxes. In each of these cases however, the analog
18 programming signal received by the digital video recorder is an analog version of the
19 original digital programming signal. The conversion of the original digital programming
20 signal to an analog programming signal introduces errors that can significantly lessen the
21 quality of the digital recording that is ultimately stored on the digital video recorder.
22 Because the signal received by the digital video recorder is an analog signal, it must be
23 encoded before it may be digitally recorded, a process that also introduces additional error
24 and degradation into the stored version of the original digital signal.

1 For example, Figure 1 illustrates a conventional satellite receiver 110 connected
2 with a digital video recorder 150 and illustrates how the quality of a video stream is
3 degraded. The programming content 212 is received at the satellite receiver 110 where it is
4 tuned and demodulated by a tuner 114 and a demodulator 116 to produce a transport
5 stream. The transport demultiplexor 118 demultiplexes the transport stream to produce a
6 video stream that is decoded by the decoder 122 to produce the audio outputs 126 and
7 video output 124, which are analog signals.

8 The analog audio outputs 126 and video output 124 are received at the digital video
9 recorder 150 and converted back to a digital signal by digitizer 152. The re-digitized
10 signals have to be re-encoded by the encoder 154 to reproduce the original video stream
11 output by the transport demultiplexor 118. Unfortunately, the video stream output by the
12 encoder 154 has been degraded by the re-digitizing and re-encoding processes. This
13 degraded video stream may be recorded on the storage 156 as a recording 157. The
14 recording 157 can be decoded by the decoder 158 to produce audio outputs 160 and video
15 output 162, which are rendered, for example, by a television. Again, the audio outputs 160
16 and the video output 162 are of lesser quality than the audio outputs 126 and the video
17 output 124 because the original video stream generated by the transport demultiplexor 118
18 had to be re-digitized and re-encoded in order to be recorded on the storage 156.

SUMMARY OF THE INVENTION

The present invention relates to systems and methods for recording programming content. The present invention also relates to an integrated architecture that permits programming content to be recorded without a corresponding loss of quality in the recorded programming content. Most set top boxes that receive digital programming content, such as satellite receivers, have a single digital tuner. One feature of the present invention is the ability to decouple the tuner such that the digital programming content may be stored on a storage medium such as a hard drive or other computer-readable medium.

When the tuner is being used to record the digital programming content, the user is not able to tune other channels that may be included in the programming content. However, the user has the option of viewing the channel that is being recorded or the user may view another program or channel that has already been stored or recorded on the storage medium. In this manner, the present invention enables one channel to be recorded while previously recorded programming content is viewed in a single tuner environment.

Decoupling the tuner in this manner also provides other advantages. For example, the present invention provides systems and methods for recording the digital programming content before the programming content is decoded. More specifically, the programming content may be recorded as it was received from the programming content provider without degrading the original video stream. .

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by the practice of the invention. The features and advantages of the invention may be realized and obtained by means of the instruments and combinations particularly

FILED
69862250

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24

pointed out in the appended claims. These and other features of the present invention will become more fully apparent from the following description and appended claims, or may be learned by the practice of the invention as set forth hereinafter.

1 **BRIEF DESCRIPTION OF THE DRAWINGS**

2 In order that the manner in which the above recited and other advantages and
3 features of the invention are obtained, a more particular description of the invention briefly
4 described above will be rendered by reference to specific embodiments thereof which are
5 illustrated in the appended drawings. Understanding that these drawings depict only
6 typical embodiments of the invention and are not therefore to be considered to be limiting
7 of its scope, the invention will be described and explained with additional specificity and
8 detail through the use of the accompanying drawings in which:

9 Figure 1 represents a prior art system for recording programming content and
10 illustrate the degradation of a video stream;

11 Figure 2 illustrates an exemplary system that provides a suitable operating
12 environment for the present invention;

13 Figure 3 illustrates a satellite system that transmits programming content from a
14 content provider to a set top box via a satellite; and

15 Figure 4 illustrates an exemplary set top box including a tuner whereby the
16 programming content may be recorded on a storage medium without degrading the
17 programming content.

DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to recording digital programming content. In one embodiment, the programming content is recorded in the background. In other words, the tuner is effectively decoupled in a manner that permits the programming content to be background recorded while the set top box displays other digital programming content. The present invention also addresses the need of being able to record digital programming content without degrading or lowering the quality of the digital programming content. Degrading the quality of the digital programming content is avoided by storing the digital programming content before it is decoded and converted to an analog signal. By avoiding these procedures, which lower the quality of the programming content each time the programming content is encoded and decoded, the original quality of the programming content can be maintained when the recorded programming content is viewed by a user.

The present invention extends to both systems and methods for recording digital programming content without degrading the programming content. The embodiments of the present invention may comprise a special purpose or general purpose computer including various computer hardware, as discussed in greater detail below.

Embodiments within the scope of the present invention also include computer-readable media for carrying or having computer-executable instructions or data structures stored thereon. Such computer-readable media can be any available media which can be accessed by a general purpose or special purpose computer. One example of a special purpose computer is a set top box. By way of example, and not limitation, such computer-readable media can comprise RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code means in the form of computer-

1 executable instructions or data structures and which can be accessed by a general purpose
2 or special purpose computer. When information is transferred or provided over a network
3 or another communications connection (either hardwired, wireless, or a combination of
4 hardwired or wireless) to a computer, the computer properly views the connection as a
5 computer-readable medium. Thus, any such a connection is properly termed a computer-
6 readable medium. Combinations of the above should also be included within the scope of
7 computer-readable media. Computer-executable instructions comprise, for example,
8 instructions and data which cause a general purpose computer, special purpose computer,
9 or special purpose processing device to perform a certain function or group of functions.

10 Figure 2 and the following discussion are intended to provide a brief, general
11 description of a suitable computing environment in which the invention may be
12 implemented. Although not required, the invention will be described in the general context
13 of computer-executable instructions, such as program modules, being executed by
14 computers in network environments. Generally, program modules include routines,
15 programs, objects, components, data structures, etc. that perform particular tasks or
16 implement particular abstract data types. Computer-executable instructions, associated
17 data structures, and program modules represent examples of the program code means for
18 executing steps of the methods disclosed herein. The particular sequence of such
19 executable instructions or associated data structures represent examples of corresponding
20 acts for implementing the functions described in such steps.

21 Those skilled in the art will appreciate that the invention may be practiced in
22 network computing environments with many types of computer system configurations,
23 including set top boxes, personal computers, hand-held devices, multi-processor systems,
24 microprocessor-based or programmable consumer electronics, network PCs,

1 minicomputers, mainframe computers, and the like. The invention may also be practiced
2 in distributed computing environments where tasks are performed by local and remote
3 processing devices that are linked (either by hardwired links, wireless links, or by a
4 combination of hardwired or wireless links) through a communications network. In a
5 distributed computing environment, program modules may be located in both local and
6 remote memory storage devices.

7 With reference to Figure 2, an exemplary system for implementing the invention
8 includes a general purpose computing device in the form of a conventional computer 20,
9 including a processing unit 21, a system memory 22, and a system bus 23 that couples
10 various system components including the system memory 22 to the processing unit 21.
11 The system bus 23 may be any of several types of bus structures including a memory bus
12 or memory controller, a peripheral bus, and a local bus using any of a variety of bus
13 architectures. The system memory includes read only memory (ROM) 24 and random
14 access memory (RAM) 25. A basic input/output system (BIOS) 26, containing the basic
15 routines that help transfer information between elements within the computer 20, such as
16 during start-up, may be stored in ROM 24.

17 The computer 20 may also include a magnetic hard disk drive 27 for reading from
18 and writing to a magnetic hard disk 39, a magnetic disk drive 28 for reading from or
19 writing to a removable magnetic disk 29, and an optical disk drive 30 for reading from or
20 writing to removable optical disk 31 such as a CD-ROM or other optical media. The
21 magnetic hard disk drive 27, magnetic disk drive 28, and optical disk drive 30 are
22 connected to the system bus 23 by a hard disk drive interface 32, a magnetic disk drive-
23 interface 33, and an optical drive interface 34, respectively. The drives and their
24 associated computer-readable media provide nonvolatile storage of computer-executable

1 instructions, data structures, program modules and other data for the computer 20.
2 Although the exemplary environment described herein employs a magnetic hard disk 39, a
3 removable magnetic disk 29 and a removable optical disk 31, other types of computer
4 readable media for storing data can be used, including magnetic cassettes, flash memory
5 cards, digital video disks, Bernoulli cartridges, RAMs, ROMs, and the like.

6 Program code means comprising one or more program modules may be stored on
7 the hard disk 39, magnetic disk 29, optical disk 31, ROM 24 or RAM 25, including an
8 operating system 35, one or more application programs 36, other program modules 37, and
9 program data 38. A user may enter commands and information into the computer 20
10 through keyboard 40, pointing device 42, or other input devices (not shown), such as a
11 microphone, joy stick, game pad, satellite dish, scanner, or the like. These and other input
12 devices are often connected to the processing unit 21 through a serial port interface 46
13 coupled to system bus 23. Alternatively, the input devices may be connected by other
14 interfaces, such as a parallel port, a game port or a universal serial bus (USB). A monitor
15 47 or another display device is also connected to system bus 23 via an interface, such as
16 video adapter 48. In addition to the monitor, personal computers typically include other
17 peripheral output devices (not shown), such as speakers and printers.

18 The computer 20 may operate in a networked environment using logical
19 connections to one or more remote computers, such as remote computers 49a and 49b.
20 Remote computers 49a and 49b may each be another personal computer, a server, a router,
21 a network PC, a peer device or other common network node, and typically include many or
22 all of the elements described above relative to the computer 20, although only memory
23 storage devices 50a and 50b and their associated application programs 36a and 36b have
24 been illustrated in Figure 2. The logical connections depicted in Figure 2 include a local

1 area network (LAN) 51 and a wide area network (WAN) 52 that are presented here by way
2 of example and not limitation. Such networking environments are commonplace in office-
3 wide or enterprise-wide computer networks, intranets and the Internet.

4 When used in a LAN networking environment, the computer 20 is connected to the
5 local network 51 through a network interface or adapter 53. When used in a WAN
6 networking environment, the computer 20 may include a modem 54, a wireless link, or
7 other means for establishing communications over the wide area network 52, such as the
8 Internet. The modem 54, which may be internal or external, is connected to the system bus
9 23 via the serial port interface 46. In a networked environment, program modules depicted
10 relative to the computer 20, or portions thereof, may be stored in the remote memory
11 storage device. It will be appreciated that the network connections shown are exemplary
12 and other means of establishing communications over wide area network 52 may be used.

13 Figure 3 is a block diagram that generally illustrates the transmission of
14 programming content to a set top box. The programming content 212 is representative of
15 the data, information or signals that are received by the set top box 210, and may include,
16 but is not limited to, satellite transmissions, cable television transmissions, local television
17 transmissions, radio transmissions, Internet data or transmissions, Motion Pictures Experts
18 Group (MPEG) video, video streams, audio streams, and the like or any combination
19 thereof whether analog or digital in nature. Programming content 212 also includes the
20 content carried by satellite transmissions, cable transmissions, radio transmissions, local
21 television transmissions and the like or any combination thereof.

22 Included in the programming content 212 is electronic program guide (EPG) data,
23 also referred to herein as "guide data." The guide data is usually a description of the
24 programming content 212 and may include, but is not limited to, program titles, program

1 starting times, program ending times, program ratings, program descriptions, program
2 content ratings, program duration, program reviews, and the like or any combination
3 thereof. More generally, the guide data, as used herein, refers to data or information that is
4 related to or describes the programming content 212. The guide data is usually processed
5 by the set top box 210 and displayed to a user via the display 204, which may be a
6 television set, a computer monitor, or other display device.

7 Often, the programming content 212 contains multiple channels, each of which
8 may carry a different kind of data. For instance, one channel may carry MPEG video
9 streams while another channel may carry Internet related data. In most instances, the
10 programming content 212 is compressed.

11 The content provider 200 transmits the programming content 212 to a satellite 202.
12 Each satellite 202 typically has 32 broadcast frequencies or transponders and the number
13 of channels that can be compressed onto each transponder of the satellite 202 is dependent
14 on many factors including, but not limited to, the image quality, the frame rate of the
15 source material, the amount of movement in the source material, the amount of error
16 correction overhead, and the like. Generally, each transponder can carry approximately 7
17 to 12 channels. In addition to carrying multiple channels, the programming content
18 broadcast by each transponder often includes program guide data, conditional access data,
19 and other digital information.

20 The programming content broadcast by the satellite 202 is received at the set top
21 box 210 and processed such that the data or channels may be viewed on the display device
22 204. Because multiple channels can be carried on a single transponder and each satellite
23 has multiple transponders, the antenna for the set top box 210 is capable of receiving on
24 the order of 300 channels while being pointed at a fixed position or satellite 202. While

1 the present invention is described in terms of programming content delivered via a satellite
2 system, it is understood that the systems and methods described herein may be applied to
3 cable television systems, the Internet, and other systems capable of delivering
4 programming content to a user.

5 Figure 4 is a block diagram illustrating an exemplary set top box, which represents
6 one example of a special purpose computer that can implement the invention. The set top
7 box 210 is representative of analog and digital devices including, but not limited to,
8 satellite receivers, digital recording devices, cable boxes, video game consoles, Internet
9 access boxes, and the like or any combination thereof, all of which are examples of special
10 purpose computers. Television sets integrated with set top boxes are also embraced by the
11 term "set top box." The set top box 210 typically includes portions of the general purpose
12 computer as described with reference to Figure 2. Additionally, the set top box 202 can be,
13 but does not need to be, capable of connecting with a network such as the Internet.

14 The set top box 210 typically has several components that act on the programming
15 content 212 in order to produce or display a channel on the display 204 or otherwise render
16 at least a portion of the programming content 212. The programming content 212 received
17 by the set top box 210, as illustrated in Figure 4, is typically received from a satellite as
18 illustrated in Figure 3. Upon receiving the programming content 212, the set top box 210
19 tunes to a particular transponder of the satellite using the tuner 214.

20 Next, the demodulator 216 demodulates the tuned signal and the output of the
21 demodulator 216 is a multiplexed transport stream. The output of the tuner 214 and the
22 demodulator 216 contains audio, video, and data packets which may be associated with
23 multiple channels, guide data, conditional access data, and the like. In order to separate a
24 particular channel from the transport stream, the transport 218 demultiplexes the transport

1 stream produced by the tuner 214 and the demodulator 216 to isolate a particular video
2 stream or channel included in the multiplexed transport stream.

3 In order to view or render the video stream output by the transport 218 without
4 recording the video stream, the video stream is received by the decoder 222, which
5 demultiplexes the video, audio, and other information in the transport output. From the
6 demultiplexed video, video frames are generated and output to the video out 224 in their
7 proper order. The audio output, which is generated from the demultiplexed audio, is
8 supplied at the audio outputs 226. These analog outputs are typically supplied to a display
9 device or other set top box.

10 As described with reference to Figure 3, the analog video out 224 and the analog
11 audio outputs 226 can be digitally recorded, they must first be re-digitized or converted to
12 a digital signal using an analog to digital converter and encoded. As previously described,
13 this results in a degradation of the original digital video stream. In the set top box 210
14 shown in Figure 4, this degradation of the video stream is avoided because the output of
15 the transport 218 is directed to the storage medium 220 and recorded in an encoded digital
16 format on the storage medium 220 as indicated by the dashed line 219. The storage
17 medium 220 may be a hard drive or other computer readable medium as described with
18 reference to Figure 2. Because the video stream or channel is digitally recorded as it was
19 received at the set top box, the encoded digital format may be determined from the content
20 provider.

21 A video stream or channel recorded in this manner is designated in Figure 4 as
22 recording 229. The recording 229 has not been decoded or converted to an analog form
23 and is therefore stored on the storage medium 220 as it was received in the programming
24 content 212 at the input of the set top box 210. The recording 229 does not suffer from

1 degradation that is introduced when the channel is converted to an analog signal and re-
2 encoded.

3 The recording 229, when stored from the output of the transport 218, is a digital
4 recording of the program selected by the user, has not typically been converted to an
5 analog signal, and has not been decoded. When the user decides to view the program
6 stored as the recording 229, which was stored from the output of the transport 218, the
7 recording 229 is simply decoded by the decoder 222 to generate the audio and video
8 outputs.

9 As indicated by the dashed lines 219 and 215, the output of the transport 218 can be
10 directed to the storage 220 and/or the decoder 222. Thus, the transport 218 is effectively
11 decoupled from the decoder 222 when the output of the transport 218 is directed to the
12 storage 220. More generally, the tuner 214 is also decoupled from the decoder 222
13 because the transport stream tuned by the tuner 214 is not being viewed in this example,
14 and it is possible to view a previously recorded channel while the set top box 210 is
15 recording another channel. For example, the tuner 214 may be used such that a first video
16 stream may be stored as recording 229, while a second video stream from the recording
17 230, which was previously recorded, may be decoded by the decoder 222 and presented to
18 a user on a suitable device. It is important to understand that the recording 230 was
19 recorded without decoding the recording 230 in order to minimize the degradation of the
20 recording 230. The recording 230 was also recorded from the output of the transport 218
21 as described above. In this manner, a channel may be recorded while another channel is
22 viewed in a set top box that only has a single tuner.

23 The present invention may be embodied in other specific forms without departing
24 from its spirit or essential characteristics. The described embodiments are to be considered